

### VISION SYSTEM FOR QUALITY CONTROL AND AUTOMATIC REJECTION OF NON-COMPLIANT PRODUCTS

quality

2





SENSURE STARGATE ML-C is an innovative vision system that, thanks to the use of SENSURE SYNAPSE technology, allows you to perform the quality control of highly variable products and automatically reject noncompliant ones. SENSURE STARGATE ML-C also guarantees continuous monitoring of the process with data collection and analysis, providing a real-time display and dedicated reporting.

# STARGATE ML-C

### QUALITY **CROSSES** A NEW DIMENSION

### + COMPACT AND SOLID SYSTEM

Full compliance with the requirements of the food industry.

#### +

### DEDICATED ELECTRICAL CABINET WITH OPERATOR INTERFACE

Intuitive graphic interface with the possibility of remote connection to the system.

## TOTAL PRODUCTION

Control at maximum line speed, with accurate, reliable and fast measurements.

### REAL-TIME DISPLAY, DATA COLLECTION AND REPORTING

+

Storage of the entire production data in a SQL database, which can also be integrated into third-party software.

#### + MULTIPLE MEASURABLE QUALITY PARAMETERS

Ability to perform 2D (from top and bottom) and 3D measurements to identify defects in size, shape, colour and volume.

## EASILY INTEGRATED

+ -

Possibility of exchanging signals and information with conveyors/ machines/systems. Quick installation within existing lines.

### SINGLE OR MULTIPLE REJECTION OF NON-COMPLIANTS PRODUCTS

Single reject by air nozzles or agglomerated products with traps.

### SAFE AND READY FOR INDUSTRY 4.0


+

Full compliance with safety standards and with the requirements for Industry 4.0.

### Mechanical frame and products handling



. Compact and modular stainless steel structure (the modularity of the system allows to integrate the different types of control even at different times).



Customized **conveyors for products** handling at the entrance and exit of SENSURE STARGATE ML-C.

### **DIMENSIONAL DATA**

#### Line width

from 600 mm (24") up to 2.000 mm (80")

### Total width

Line width + 800 mm (32") (without belt hopper)

### Total height

2.800 mm (110") (approx.)

### Total size

970 mm (40") (approx.)

### Height of products at entrance and exit

1.600 mm (65") (approx.) at entrance 1.000 mm (40") (approx.) at exit


### Weight

from 900 kg (2.000 lbs) to 1.600 kg (3.500 lbs) (approx.) depending on line width



Easily interchangeable polizene plate for products sliding (low friction system and compliant with regulations required in the food industry).





Air nozzles for the rejection of the single non-compliant product.



Belt hopper for the handling of the non-compliant products in a dedicated bin.




### go online

### Handling of non-compliant products

Traps for the rejection of multiple non-compliant products.







**SENSURE srl** Via Autostrada, 32 - 24126 Bergamo (BG) – Italy Tel. +39 035 319080 - info@sensure.it





www.sensure.it