


VISION INSPECTION SYSTEM FOR QUALITY CONTROL AND AUTOMATIC REJECTION OF NON-COMPLIANT PRODUCTS

quality .







SENSURE STARGATE ML-C is an innovative vision system that, thanks to the use of SENSURE SYNAPSE software suite, allows for the quality control of highly variable products and the automatic rejection of non-compliant ones. SENSURE STARGATE ML-C also ensures continuous monitoring of the process, with data collection and analysis, providing a real-time display and dedicated reporting.

# STARGATE

## QUALITY **CROSSES** A NEW DIMENSION

#### **Main features**

- Compact and solid system Full compliance with the requirements of the food industry.
- Total production control Control at maximum line speed, with accurate, reliable and fast measurements.
- Multiple measurable quality parameters Ability to perform 2D (top and bottom views) and 3D measurements to detect defects in terms of size, shape, colour, and volume.
- Single or multiple rejection of non-compliants products
   Reject single products with air nozzles or agglomerated with traps.

- Dedicated electrical cabinet with operator interface An intuitive graphic interface that allows for remote connections to the system.
- Real-time display, data collection and reporting Storage of the entire production data in a SQL database, which can also be integrated into third-party software.
- Easily integrated in line
  Possibility of exchanging signals and information with conveyors/machines/systems.
   Quick installation within existing lines.
- Safe and ready for Industry 4.0 Full compliance with safety standards and with the requirements for Industry 4.0.


## Mechanical frame and products handling




The **stainless steel structure** is compact and modular, which allows for the integration of different types of controls even at different times due to the modularity of the system.



Easily interchangeable **polizene plate for products sliding** (low-friction system compliant with food industry regulations).



**Customized conveyors** are available **for handling products** at the entrance and exit of SENSURE STARGATE ML-C.



#### **TECHNICAL DATA**

#### Line width

from 600 mm (24") up to 2.000 mm (80")

#### Total width

Line width + 800 mm (32") (without belt hopper)

#### Total height

2.800 mm (110") (approx.)

#### Total depth

970 mm (40") (approx.)

#### Height of products at entrance and exit

1.600 mm (65") (approx.) at entrance 1.000 mm (40") (approx.) at exit

#### Weight

from 900 kg (2.000 lbs) to 1.600 kg (3.500 lbs) (approx.) depending on line width

## + Vision systems



Vision points for 2D measurements from the top.




Vision points for 2D measurements from the bottom.




Vision points for 3D measurements.

## Handling of non-compliant products



Air nozzles for the rejection of the single non-compliant product.



Traps for the rejection of multiple non-compliant products.




go online



**Belt hopper** for the handling of the non-compliant products in a dedicated bin.





SENSURE srl Via Portico, 55/b 24050 Orio al Serio (BG) - Italy Tel. +39 035 319080 - info@sensure.it

www.sensure.it



